



- 1- Ethernet RJ45 connection : main connection to provide internet access to the whole device
- 2- General power supply connection
- 3- Ethernet RJ45 connection : internet connection for output devices
- 4- USB connections to server (keyboard, mouse, USB keys, printer, ...)
- 5- Microphone input to multi-touch table
- 6- Video output (VGA) from server
- 7- Sound output from multi-touch table
- 8- USB connections to multi-touch table (keyboard, mouse, USB keys, printer, ...)
- 9- Video output (HDMI) from multi-touch table
- 10- Extra power supply to connect external devices (printer, projectors, ...)



Flight case		
Weight	162 kg	
Volume of the storage compartment	≈ 450 liters	
Wheels	6 wheels (125 mm)	
Multi-touch table		
Model name	Samsung SUR 40	
Panel	Size	40 inches (101 cm)
	Display area	885.6 mm (H) × 498.1 (V)
Synchronisation	Horizontal frequency	30 ~ 81 kHz
	Vertical frequency	56 ~ 75 kHz
Display color	16.7 Million	
Resolution	1920 × 1080 60 Hz	
HDMI Input resolution	1080 p 50/60 Hz; 720 p 50/60 Hz; 576p 50 Hz; 480p 50/60 Hz	
Venue readiness Guide - especially for ambient lightning conditions	http://www.samsunglfd.com/product/feature.do?modelCd= SUR40	
Server		
A server is used to host documents and data	It can hosts data systems such as SmartPlant foundation®, DCS (Documentum®, Sharepoint®, ...), Geographic Information Systems Geo-server	
General		
Power supply	100 to 240 V	
A Connectivity	Ethernet RJ45; Wifi 802.11 b/g/n, Bluetooth 3.0 + HS	
B I/O Ports		
Additional included supply	Power supply cable (4 m) and ethernet cable (6 m)	
Environmental conditions	Operating	Temperature : 5°C - 30°C (41°F - 86°F) Humidity : 8% - 85%, non-liquefied, an altitude of 2000 m or lower
	Storage	Temperature : -20°C - 45°C (4°F - 113°F) Humidity : 8% - 95%, non-liquefied, an altitude of 3000 m or lower

* Features and specifications are subject to change without prior notification.